



SPECIFICATION : DIN 471-25 x 1.2

SHAFT DIA. : 25 mm (.984 in)
 GROOVE DIA. : 23.9 $\begin{smallmatrix} +0.00 \\ -0.21 \end{smallmatrix}$ mm (.941 $\begin{smallmatrix} +.000 \\ -.008 \end{smallmatrix}$ in)
 GROOVE WIDTH : 1.3 mm MIN (.051 in)
 MATERIAL : C75S
 HARDNESS : AUSTEMPER TO HRC 47-54

2	6/25	RG	ECN 14-305
1	12/1	WB	ECN 10-458

REV. NO.	DATE	REV. BY	ECN NUMBER	
REVISION				
WARNING: IF PRINTED, IT IS THE USERS RESPONSIBILITY TO CHECK THAT THIS DOCUMENT REFLECTS THE LATEST REVISION LEVEL.				
ALL DIMENSIONS IN MILLIMETERS				
MATERIAL	HEAT TREAT	FINISH	QTY. REQ'D.	
THE CONTENTS OF THIS DRAWING IS THE PROPERTY OF ROTOR CLIP CO., INC. AND SHALL BE RETURNED TO ROTOR CLIP CO., INC. UPON REQUEST. ANY UNAUTHORIZED DISCLOSURE OF ITS CONTENTS WITHOUT THE PERMISSION OF ROTOR CLIP CO., INC. IS PROHIBITED.				

ROTOR CLIP CO., INC.			
DSH-25 CUSTOMER DRAWING			
SCALE NONE	DRAWN BY RWG	DATE 4/24/90	
DWG. SIZE A	DWG. NO. DSH-25-2		