


14.2 MAX

SHAFT DIAMETER: 215; GROOVE DIAMETER: 209 $\frac{+0.00}{-0.72}$
 SHAFT DIAMETER: 217; GROOVE DIAMETER: 211 $\frac{+0.00}{-0.72}$
 SHAFT DIAMETER: 218; GROOVE DIAMETER: 212 $\frac{+0.00}{-0.72}$

GROOVE WIDTH: 5.15 MIN.
 MATERIAL: DIN 17 222/ DIN EN10132-4
 Ck 75/ C75S
 HARDNESS: 390-470 HV (40-47 HRC EQUIV.)

REV. NO.	DATE	REV. BY	ECN NUMBER	
REVISION				
WARNING: IF PRINTED, IT IS THE USERS RESPONSIBILITY TO CHECK THAT THIS DOCUMENT REFLECTS THE LATEST REVISION LEVEL.				
ALL DIMENSIONS IN MILLIMETERS				
MATERIAL	HEAT TREAT	FINISH		
THE CONTENTS OF THIS DRAWING ARE THE PROPERTY OF ROTOR CLIP CO. INC. AND SHALL BE RETURNED TO ROTOR CLIP CO. INC. UPON REQUEST. ANY UNAUTHORIZED DISCLOSURE OF ITS CONTENTS WITHOUT THE PERMISSION OF ROTOR CLIP CO. INC. IS PROHIBITED.				

ROTOR CLIP CO., INC.			
CUSTOMER DRAWING DSH-215			
SCALE NONE	DRAWN BY RDS	DATE 01/10/11	
DWG. SIZE A	DWG. NO. DSH-215-OIL-BS-2		