



SHAFT DIAMETER : 26.0  
 GROOVE DIAMETER : 24.9 <sup>+0.00</sup>/<sub>-0.21</sub>  
 GROOVE WIDTH : 1.3 MIN.  
 HARDNESS : 47-54 HRC  
 MATERIAL : SAE 1060-1090  
 SPECIFICATION : DIN 471-26

ALL DIMENSIONS IN MILLIMETERS

1 | 2/16 | GF | ECN 12-077

REV. NO.	DATE	REV. BY	ECN NUMBER		<b>ROTOR CLIP CO., INC. ®</b>			
<b>REVISION</b>				CUSTOMER DRAWING				
WARNING: IF PRINTED, IT IS THE USERS RESPONSIBILITY TO CHECK THAT THIS DOCUMENT REFLECTS THE LATEST REVISION LEVEL.					DSH-26			
TOLERANCES UNLESS OTHERWISE SPECIFIED		3 PLACE DEC. ±.005	4 PLACE DEC. ±.0005	FRACT. ±1/64	(GD17, DSH262)			
MATERIAL	HEAT TREAT	FINISH	QTY. REQ'D.		SCALE	DRAWN BY	DATE	FILE NAME:
THE CONTENTS OF THIS DRAWING IS THE PROPERTY OF ROTOR CLIP CO., INC. AND SHALL BE RETURNED TO ROTOR CLIP CO., INC. UPON REQUEST. ANY UNAUTHORIZED DISCLOSURE OF ITS CONTENTS WITHOUT THE PERMISSION OF ROTOR CLIP CO., INC. IS PROHIBITED.					NONE	RWG	11/22/93	
					DWG. SIZE	DWG. NO.		
					A	DSH-26-2		