



SHAFT DIA.: 30.0

GROOVE DIA.: 28.6 $\begin{smallmatrix} +0.00 \\ -0.21 \end{smallmatrix}$

GROOVE WIDTH: 1.60 MIN.

MATERIAL: HIGH CARBON SPRING STEEL

HARDNESS: 470-580 HV (47-54 HRC EQUIV)

ALL DIMENSIONS IN mm

DIN SPECIFICATION: 471-30

REV. NO.	DATE	REV. BY	CH'KD BY	DESCRIPTION	ROTOR CLIP CO., INC.			
REVISION								
TOLERANCE UNLESS OTHERWISE SPECIFIED		3 PLACE DEC. 4 PLACE DEC.	FRACT. ANGLES		CUSTOMER DRAWING DSH-30 (DSH302)			
MATERIAL	HEAT TREAT	FINISH						
THE CONTENTS OF THIS DWG. IS THE PROPERTY OF ROTOR CLIP CO., INC. AND SHALL BE RETURNED TO ROTOR CLIP CO., INC. UPON REQUEST. ANY UNAUTHORIZED DISCLOSURE OF ITS CONTENTS IS PROHIBITED WITHOUT THE PERMISSION OF ROTOR CLIP CO., INC.					SCALE: NONE	DRAWN BY: DGM	DATE: 040894	CH'K'D./APPROVED BY:
					DWG. SIZE: A	DWG. NO. DSH-30-2		