



SHAFT DIA.: 32.0

GROOVE DIA.: 30.3 $\begin{smallmatrix} +0.00 \\ -0.25 \end{smallmatrix}$

GROOVE WIDTH: 1.60 MIN.

MATERIAL: HIGH CARBON SPRING STEEL

HARDNESS: 470-580 HV (47-54 HRC EQUIV)

ALL DIMENSIONS IN mm

REV. NO.	DATE	REV. BY	CHK'D BY	DESCRIPTION	ROTOR CLIP CO., INC.			
REVISION								
TOLERANCE UNLESS OTHERWISE SPECIFIED		3 PLACE DEC. 4 PLACE DEC.		FRACT. ANGLES	CUSTOMER DRAWING DSH-32 (DSH322)			
MATERIAL	HEAT TREAT	FINISH						
THE CONTENTS OF THIS DWG. IS THE PROPERTY OF ROTOR CLIP CO., INC. AND SHALL BE RETURNED TO ROTOR CLIP CO., INC. UPON REQUEST. ANY UNAUTHORIZED DISCLOSURE OF ITS CONTENTS IS PROHIBITED WITHOUT THE PERMISSION OF ROTOR CLIP CO., INC.					SCALE:	DRAWN BY:	DATE:	CHK'D./APPROVED BY:
					NONE		DGM	032594
					DWG. SIZE:	DWG. NO.		
					A		DSH-32-2	

DRAWING 7/726 FORM # 3386