


4 PRONGS EQUALLY SPACED

MAT'L: HIGH CARBON SPRING STEEL

HARDNESS: 15N SCALE 83-85.5

ALL DIM'S ARE IN mm

REV. NO.	DATE	REV. BY	ECN NUMBER		ROTOR CLIP CO., INC. 			
<b>REVISION</b> WARNING: IF PRINTED, IT IS THE USERS RESPONSIBILITY TO CHECK THAT THIS DOCUMENT REFLECTS THE LATEST REVISION LEVEL.					CUSTOMER RING DRAWING DTX-4			
TOLERANCES UNLESS OTHERWISE SPECIFIED		3 PLACE DEC. 4 PLACE DEC.		FRACT. ANGLES				
MATERIAL	HEAT TREAT	FINISH	QTY. REQ'D.		SCALE	DRAWN BY	DATE	FILE NAME:
THE CONTENTS OF THIS DRAWING IS THE PROPERTY OF ROTOR CLIP CO. INC. AND SHALL BE RETURNED TO ROTOR CLIP CO. INC. UPON REQUEST. ANY UNAUTHORIZED DISCLOSURE OF ITS CONTENTS WITHOUT THE PERMISSION OF ROTOR CLIP CO. INC. IS PROHIBITED.					NONE	SJF	091401	(DTX42.DRW)
					DWG. SIZE	DWG. NO.		
					A	DTX-4-2		