


8 PRONGS ARE EQUALLY SPACED

SHAFT DIA:  $\phi 20.00(+0.00/-0.13)$   
 GROOVE DIA:  $\phi 19.75(+0.00/-0.13)$   
 GROOVE WIDTH: 1.0 MIN  
 MAT'L: HIGH CARBON SPRING STEEL  
 HARDNESS: 83-85.5 HR15N

ALL DIMENSIONS ARE IN MILLIMETERS

REV. NO.	DATE	REV. BY	ECN NUMBER		<b>ROTOR CLIP CO., INC.</b> 
REVISION				CUSTOMER DRAWING DTX-20	
WARNING: IF PRINTED, IT IS THE USERS RESPONSIBILITY TO CHECK THAT THIS DOCUMENT REFLECTS THE LATEST REVISION LEVEL.					SCALE NONE
TOLERANCES UNLESS OTHERWISE SPECIFIED		3 PLACE DEC. $\pm 0.005$	4 PLACE DEC. $\pm 0.0005$	FRACT. $\pm 1/64$	
MATERIAL	HEAT TREAT	FINISH	QTY. REQ'D.		DATE 9/18/06
THE CONTENTS OF THIS DRAWING ARE THE PROPERTY OF ROTOR CLIP CO. INC. AND SHALL BE RETURNED TO ROTOR CLIP CO. INC. UPON REQUEST. ANY UNAUTHORIZED DISCLOSURE OF ITS CONTENTS WITHOUT THE PERMISSION OF ROTOR CLIP CO. INC. IS PROHIBITED.					FILENAME:
					DWG. SIZE A