

SHAFT DIA: 6.0

GROOVE DIA: 5.0+8:09

GROOVE WIDTH: 0.74 MIN

MATERIAL: HIGH CARBON SPRING STEEL

HARDNESS: 485-545 HV (48-52 HRC EQUIV)

. ALL DIMENSIONS ARE IN mm

| REV. DATE REV | E | ECN NUMBER | | | DOTOD CLID OO ING | | | | |
|---|-------------------|------------|--|--------------------------|-------------------|-------------|------------|----|--|
| REVISION WARNING: IF PRINTED, IT IS THE USERS RESPONSIBILITY TO CHECK THAT | | | | ROTOR CLIP CO.,INC. (R) | | | | | |
| WARNING: IF PRINTED, IT IS THE USERS RESPONSIBILITY TO CHECK THAT THIS DOCUMENT REFLECTS THE LATEST REVISION LEVEL. MATERIAL HEAT TREAT FINISH QTY, REQ'D. | | | | DC-6 CUSTOMER DRAWING | | | | | |
| | THIS DRAWING IS T | | | SCALE NONE | DRAWN BY | DATE 9/5/00 | FILE NAME: | 2) | |
| AND SHALL BE RETURNED TO ROTOR CLIP CO.INC. UPON REQUEST. ANY UNAUTHORIZED DISCLOSURE OF ITS CONTENTS WITHOUT THE PERMISSION OF ROTOR CLIP CO.INC. IS PROHIBITED. | | | | DWG. SIZE | DWG, NO. | DC-6-2 | | | |