


5 PRONGS ARE EQUALLY SPACED

MAT'L: HIGH CARBON SPRING STEEL

HARDNESS: 83-85.5 HR15N

ALL DIMENSIONS ARE IN MILLIMETERS

REV. NO.	DATE	REV. BY	ECN NUMBER		ROTOR CLIP CO., INC. 				
REVISION				CUSTOMER DRAWING DTX-7					
WARNING: IF PRINTED, IT IS THE USERS RESPONSIBILITY TO CHECK THAT THIS DOCUMENT REFLECTS THE LATEST REVISION LEVEL.					SCALE NONE DRAWN BY GWF DATE 12/27/99 FILENAME:				
TOLERANCES UNLESS OTHERWISE SPECIFIED		3 PLACE DEC. ±.005		FRACT. ± 1/64					4 PLACE DEC. ±.0005
MATERIAL		HEAT TREAT		FINISH		QTY. REQ'D.		DWG. NO.	
THE CONTENTS OF THIS DRAWING ARE THE PROPERTY OF ROTOR CLIP CO. INC. AND SHALL BE RETURNED TO ROTOR CLIP CO. INC. UPON REQUEST. ANY UNAUTHORIZED DISCLOSURE OF ITS CONTENTS WITHOUT THE PERMISSION OF ROTOR CLIP CO. INC. IS PROHIBITED.					A		DTX-7-2		