



SHAFT DIA RANGE: 10.0-14.0

GROOVE DIA: 9.0 +0.00

GROOVE WIDTH: 1.15 +0.08

MAT'L: HIGH CARBON SPRING STEEL

HARDNESS: 46-54 HRC

DIN SPECIFICATION: 6799-9

REV.	DATE	REV. BY	E	CN NUMBI	ER					
REVISION WARNING: IF PRINTED, IT IS THE USERS RESPONSIBILITY TO CHECK THAT						ROTOR CLIP CO.,INC.				
	THIS DOCUMENT REFLECTS THE LATEST REVISION LEVEL.						CUSTOMER RING DRAWING			
TOLERANCES UNLESS 3 PLACE DEC. FRACT. OTHERWISE SPECIFIED 4 PLACE DEC. ANGLES						DE-9				
M	ATERIA	L	HEAT TREAT	FINISH	QTY. REQ'D.		1		Γ	
THE (CONTEN	TS OF	THIS DRAWING IS	THE PROPERTY OF	ROTOR CLIP CO INC.	NONE	SJF	022692	FILE NAME: (DE92.DRW)	
AND S UNAU	THE CONTENTS OF THIS DRAWING IS THE PROPERTY OF ROTOR CLIP CO.INC. AND SHALL BE RETURNED TO ROTOR CLIP CO.INC. UPON REQUEST. ANY UNAUTHORIZED DISCLOSURE OF ITS CONTENTS WITHOUT THE PERMISSION OF ROTOR CLIP CO.INC. IS PROHIBITED.						DE-9-2			