

SHAFT DIA RANGE: 2.0-2.5

GROOVE DIA: $1.5^{+0}_{-0.06}$

GROOVE WIDTH: $0.44^{+0}_{-0.04}$


MATERIAL: DIN 17 222/DIN EN 10132-4
Ck 75/C75S

HARDNESS: 460-580 HV (46-54 HRC EQUIV)

ALT MATERIAL: DIN 1.4122 (x39CrMo17)

HARDNESS: 470-580 HV (47-54 HRC EQUIV)

1	2/22	WB	ECN 16-075	
REV. NO.	DATE	REV. BY	ECN NUMBER	
REVISION				
WARNING: IF PRINTED, IT IS THE USERS RESPONSIBILITY TO CHECK THAT THIS DOCUMENT REFLECTS THE LATEST REVISION LEVEL.				
MATERIAL	HEAT TREAT	FINISH	QTY. REQ'D.	
THE CONTENTS OF THIS DRAWING IS THE PROPERTY OF ROTOR CLIP CO. INC. AND SHALL BE RETURNED TO ROTOR CLIP CO. INC. UPON REQUEST. ANY UNAUTHORIZED DISCLOSURE OF ITS CONTENTS WITHOUT THE PERMISSION OF ROTOR CLIP CO. INC. IS PROHIBITED.				

ROTOR CLIP CO., INC. 			
DE-1.5 CUSTOMER DRAWING			
SCALE NONE	DRAWN BY WB	DATE 6/5/92	FILE NAME:
DWG. SIZE A	DWG. NO. DE-1.5-2		