


BORE DIAMETER: 160  
 GROOVE DIAMETER: 165 <sup>+0.63</sup>/<sub>-0.00</sub>  
 GROOVE WIDTH: 4.15 MIN.  
 MATERIAL: DIN 17 222/ DIN EN10132-4  
 Ck 75/ C75S  
 HARDNESS: 435-530 HV (44-51 HRC EQUIV.)

ALL DIMENSIONS ARE IN MILLIMETERS

|  |            |         |             |  |   |  |  |  |
|--|------------|---------|-------------|--|---|--|--|--|
| REV. NO.   | DATE       | REV. BY | ECN NUMBER  |  | <b>ROTOR CLIP CO., INC.</b>  |  |  |  |
| REVISION<br>WARNING: IF PRINTED, IT IS THE USERS RESPONSIBILITY TO CHECK THAT THIS DOCUMENT REFLECTS THE LATEST REVISION LEVEL.  |            |         |             | CUSTOMER DRAWING<br>DHO-160              |   |  |  |  |
| ALL DIMENSIONS IN MILLIMETERS  |            |         |             |  |   |  |  | SCALE NONE    DRAWN BY RDS    DATE 1/7/11    FILENAME: |
| MATERIAL   | HEAT TREAT | FINISH  | QTY. REQ'D. | DWG. SIZE A    DWG. NO. DHO-160-OIL-BS-2 |   |  |  |  |
| THE CONTENTS OF THIS DRAWING ARE THE PROPERTY OF ROTOR CLIP CO. INC. AND SHALL BE RETURNED TO ROTOR CLIP CO. INC. UPON REQUEST. ANY UNAUTHORIZED DISCLOSURE OF ITS CONTENTS WITHOUT THE PERMISSION OF ROTOR CLIP CO. INC. IS PROHIBITED. |            |         |             |  |   |  |  |  |