



BORE DIA: 16.0
 GROOVE DIA: 16.8 ± 0.11
 GROOVE WIDTH: 1.10 MIN
 MATERIAL: HIGH CARBON SPRING STEEL
 HARDNESS: 470-580 HV (HR_c 47-54 EQIV)

ALL DIMENSIONS ARE IN mm

| | | | | | |
|--|------------|------------------------------|---------------|-------------|--|
| REV. NO. | DATE | REV. BY | CHK'D BY | DESCRIPTION | ROTOR CLIP CO., INC. |
| REVISION | | | | | |
| TOLERANCE UNLESS OTHERWISE SPECIFIED | | 3 PLACE DEC. 4 PLACE DEC. | FRACT. ANGLES | | DHO-16 CUSTOMER DRAWING DHO162.DRW |
| MATERIAL | HEAT TREAT | FINISH | | | |
| THE CONTENTS OF THIS DWG. IS THE PROPERTY OF ROTOR CLIP CO., INC. AND SHALL BE RETURNED TO ROTOR CLIP CO., INC. UPON REQUEST. ANY UNAUTHORIZED DISCLOSURE OF ITS CONTENTS IS PROHIBITED WITHOUT THE PERMISSION OF ROTOR CLIP CO., INC. | | | | | SCALE: NONE |
| | | | | | DWG. SIZE: A |
| | | | | | DWG. NO. DHO-16-2 |

BRUNING 77726 FORM # 3386