


BORE DIAMETER: 255; GROOVE DIAMETER: 263 $\begin{matrix} +0.81 \\ -0.00 \end{matrix}$
 BORE DIAMETER: 257; GROOVE DIAMETER: 265 $\begin{matrix} +0.81 \\ -0.00 \end{matrix}$

GROOVE WIDTH: 5.15 MIN.
 MATERIAL: DIN 17 222/ DIN EN10132-4
 Ck 75/ C75S
 HARDNESS: 390-470 HV (40-47 HRC EQUIV.)

REV. NO.	DATE	REV. BY	ECN NUMBER		ROTOR CLIP CO., INC. 
REVISION WARNING: IF PRINTED, IT IS THE USERS RESPONSIBILITY TO CHECK THAT THIS DOCUMENT REFLECTS THE LATEST REVISION LEVEL.				CUSTOMER DRAWING DHO-255	
ALL DIMENSIONS IN MILLIMETERS					SCALE NONE DRAWN BY RDS DATE 01/07/11
MATERIAL	HEAT TREAT	FINISH			
THE CONTENTS OF THIS DRAWING ARE THE PROPERTY OF ROTOR CLIP CO. INC. AND SHALL BE RETURNED TO ROTOR CLIP CO. INC. UPON REQUEST. ANY UNAUTHORIZED DISCLOSURE OF ITS CONTENTS WITHOUT THE PERMISSION OF ROTOR CLIP CO. INC. IS PROHIBITED.					