



BORE DIA: 33.0

GROOVE DIA: 34.7 $\begin{matrix} +0.00 \\ -0.06 \end{matrix}$

GROOVE WIDTH: 1.30 MIN

MATERIAL: HIGH CARBON SPRING STEEL

HARDNESS: 470-580 HV (47-54 HRC)

ALL DIMENSIONS ARE IN mm

REV. NO.	DATE	REV. BY	ECN NUMBER		ROTOR CLIP CO., INC.			
REVISION				CUSTOMER RING DRAWING DHO-33				
TOLERANCES UNLESS OTHERWISE SPECIFIED		3 PLACE DEC. $\pm .005$	4 PLACE DEC. $\pm .0005$	FRACT. ANGLES $\pm 1/64$				
MATERIAL	HEAT TREAT	FINISH	QTY. REQ'D.					
THE CONTENTS OF THIS DRAWING IS THE PROPERTY OF ROTOR CLIP CO., INC. AND SHALL BE RETURNED TO ROTOR CLIP CO., INC. UPON REQUEST. ANY UNAUTHORIZED DISCLOSURE OF ITS CONTENTS WITHOUT THE PERMISSION OF ROTOR CLIP CO., INC. IS PROHIBITED.					SCALE NONE	DRAWN BY SJF	DATE 081595	FILE NAME: (DHO332.DRW)
					DWG. SIZE A	DWG. NO. DHO-33-2		