



BORE DIA:  $\phi 46$   
 GROOVE DIA:  $\phi 48.63 \pm 0.13$   
 GROOVE WIDTH: 1.85 MIN  
 MAT'L: DIN 17 222/ DIN EN 10132-4  
 Ck 75/C75S

HARDNESS: HRC 44-51

ALTERNATE MATERIAL: DIN 1.4122 (X39CrMo17)  
 HARDNESS: HRC 47-54

1 | 8/9 | | ECN 2011-383

REV. NO.	DATE	REV. BY	ECN NUMBER		<b>ROTOR CLIP CO., INC.</b>	
REVISION				CUSTOMER DRAWING		
WARNING: IF PRINTED, IT IS THE USERS RESPONSIBILITY TO CHECK THAT THIS DOCUMENT REFLECTS THE LATEST REVISION LEVEL.				DHO-46		
TOLERANCES UNLESS OTHERWISE SPECIFIED		3 PLACE DEC. $\pm 0.005$	4 PLACE DEC. $\pm 0.0005$	FRACT. $\pm 1/64$		
MATERIAL	HEAT TREAT	FINISH	QTY. REQ'D.		SCALE	DRAWN BY
THE CONTENTS OF THIS DRAWING ARE THE PROPERTY OF ROTOR CLIP CO. INC. AND SHALL BE RETURNED TO ROTOR CLIP CO. INC. UPON REQUEST. ANY UNAUTHORIZED DISCLOSURE OF ITS CONTENTS WITHOUT THE PERMISSION OF ROTOR CLIP CO. INC. IS PROHIBITED.				NONE	GWf	DATE
				DWG. SIZE	DWG. NO.	
				A		