


BORE DIA: 55.0  
 GROOVE DIA: 58.0(+0.30/-0.00)  
 GROOVE WIDTH: 2.15 MIN  
 MAT'L: HIGH CARBON SPRING STEEL  
 HARDNESS: 435-530 HV (44-51 HRC)

ADD DIMENSIONS ARE IN MILLIMETERS

1 | 9/24 | GF | ECN 99-311

REV. NO.	DATE	REV. BY	ECN NUMBER		<b>ROTOR CLIP CO., INC.</b> 			
REVISION WARNING: IF PRINTED, IT IS THE USERS RESPONSIBILITY TO CHECK THAT THIS DOCUMENT REFLECTS THE LATEST REVISION LEVEL.				CUSTOMER DRAWING DHO-55				
TOLERANCES UNLESS OTHERWISE SPECIFIED		3 PLACE DEC. ±.005	FRACT. ± 1/64					
		4 PLACE DEC. ±.0005	ANGLES					
MATERIAL	HEAT TREAT	FINISH	QTY. REQ'D.		SCALE	DRAWN BY	DATE	FILENAME:
THE CONTENTS OF THIS DRAWING ARE THE PROPERTY OF ROTOR CLIP CO. INC. AND SHALL BE RETURNED TO ROTOR CLIP CO. INC. UPON REQUEST. ANY UNAUTHORIZED DISCLOSURE OF ITS CONTENTS WITHOUT THE PERMISSION OF ROTOR CLIP CO. INC. IS PROHIBITED.				SCALE	DRAWN BY	DATE	FILENAME:	
				DWG. SIZE	DWG. NO.			
				A	DHO-55-2			