



BORE DIA: 42
 GROOVE DIA: 44.5 ^{+0.025}/_{-0.000}
 GROOVE WIDTH: 1.85 MIN
 ③ MAT'L: C75S
 HARDNESS: AUSTEMPER TO 470 - 580 HV (47-54 HRC EQUIV.)
 DIN 472 42 x 1.75

3 6/25 ECN 14-303
 2 10/4 GF ECN 00-282
 1 8/25 GF ECN 99-267

ALL DIMENSIONS ARE IN MILLIMETERS

REV. NO.	DATE	REV. BY	ECN NUMBER	ROTOR CLIP CO., INC.			
REVISION WARNING: IF PRINTED, IT IS THE USERS RESPONSIBILITY TO CHECK THAT THIS DOCUMENT REFLECTS THE LATEST REVISION LEVEL.							
TOLERANCES UNLESS OTHERWISE SPECIFIED		3 PLACE DEC. ±.005	4 PLACE DEC. ±.0005	FRACT. ± 1/64		ANGLES	
MATERIAL	HEAT TREAT	FINISH	QTY. REQ'D.	SCALE	DRAWN BY	DATE	
THE CONTENTS OF THIS DRAWING ARE THE PROPERTY OF ROTOR CLIP CO. INC. AND SHALL BE RETURNED TO ROTOR CLIP CO. INC. UPON REQUEST. ANY UNAUTHORIZED DISCLOSURE OF ITS CONTENTS WITHOUT THE PERMISSION OF ROTOR CLIP CO. INC. IS PROHIBITED.				NONE	GWf	8/25/99	
				DWG. SIZE	DWG. NO.		
				A	DHO-42-2		