



SHAFT DIA: .688

GROOVE DIA: .646 ± .003 .004 F.I.M.

GROOVE WIDTH: .062 ± .003

MATERIAL: SAE 1060-1090

HARDNESS: 66-71 HR30N (47-53 HRC EQUIV)

11/2001 | WB | REDREW BY CAD W/O CHANGE

REV. NO.	DATE	REV. BY	ECN NUMBER		
REVISION					
WARNING: IF PRINTED, IT IS THE USERS RESPONSIBILITY TO CHECK THAT THIS DOCUMENT REFLECTS THE LATEST REVISION LEVEL.					
TOLERANCES UNLESS OTHERWISE SPECIFIED		3 PLACE DEC. ±.005	4 PLACE DEC. ±.0005	FRACT. ±1/64	ANGLES
MATERIAL	HEAT TREAT	FINISH	QTY. REQ'D.		
THE CONTENTS OF THIS DRAWING IS THE PROPERTY OF ROTOR CLIP CO., INC. AND SHALL BE RETURNED TO ROTOR CLIP CO., INC. UPON REQUEST. ANY UNAUTHORIZED DISCLOSURE OF ITS CONTENTS WITHOUT THE PERMISSION OF ROTOR CLIP CO., INC. IS PROHIBITED.					

ROTOR CLIP CO., INC.

BSH-68
CUSTOMER DRAWING

SCALE NONE	DRAWN BY TM	DATE 11/18/85	FILE NAME: (BSH682)
---------------	----------------	------------------	------------------------

DWG. SIZE A	DWG. NO. BSH-68-2
----------------	----------------------