


BORE DIA: 1.125

GROOVE DIA: 1.197±.004 .005 F.I.M.

GROOVE WIDTH: .056±.004

MATERIAL: SAE 1060-1090

HARDNESS: 47-52 HRC

| | | | | | | | | |
|---|------------|--------------------|---------------------|--------------|--|----------------------|-----------------|------------------------|
| REV. NO. | DATE | REV. BY | ECN NUMBER | | ROTOR CLIP CO., INC.  | | | |
| REVISION | | | | | HO-112 CUSTOMER DRAWING | | | |
| WARNING: IF PRINTED, IT IS THE USERS RESPONSIBILITY TO CHECK THAT THIS DOCUMENT REFLECTS THE LATEST REVISION LEVEL. | | | | | | | | |
| TOLERANCES UNLESS OTHERWISE SPECIFIED | | 3 PLACE DEC. ±.005 | 4 PLACE DEC. ±.0005 | FRACT. ±1/64 | ANGLES | | | |
| MATERIAL | HEAT TREAT | FINISH | QTY. REQ'D. | | SCALE NONE | DRAWN BY WB | DATE 3/21/02 | FILE NAME: (HO1122) |
| THE CONTENTS OF THIS DRAWING IS THE PROPERTY OF ROTOR CLIP CO. INC. AND SHALL BE RETURNED TO ROTOR CLIP CO. INC. UPON REQUEST. ANY UNAUTHORIZED DISCLOSURE OF ITS CONTENTS WITHOUT THE PERMISSION OF ROTOR CLIP CO. INC. IS PROHIBITED. | | | | | DWG. SIZE A | DWG. NO. HO-112-2 | | |