



BORE DIA= .625

GROOVE DIA= $.665 \pm .002$.004 F.I.M.

GROOVE WIDTH= $.039^{+.003}_{.000}$

MATERIAL= SAE 1060-1090

HARDNESS= 67.5-72 HR30N (49-54 HRC EQUIV)

REV. NO.	DATE	REV. BY	ECN NUMBER		ROTOR CLIP CO., INC. ®		
REVISION WARNING: IF PRINTED, IT IS THE USERS RESPONSIBILITY TO CHECK THAT THIS DOCUMENT REFLECTS THE LATEST REVISION LEVEL.					HO-62 CUSTOMER DRAWING		
TOLERANCES UNLESS OTHERWISE SPECIFIED		3 PLACE DEC. $\pm .005$	4 PLACE DEC. $\pm .0005$	FRACT. ANGLES	$\pm 1/64$		
MATERIAL	HEAT TREAT	FINISH	QTY. REQ'D.		SCALE	DRAWN BY	DATE
THE CONTENTS OF THIS DRAWING IS THE PROPERTY OF ROTOR CLIP CO. INC. AND SHALL BE RETURNED TO ROTOR CLIP CO. INC. UPON REQUEST. ANY UNAUTHORIZED DISCLOSURE OF ITS CONTENTS WITHOUT THE PERMISSION OF ROTOR CLIP CO. INC. IS PROHIBITED.					NONE	WB	5/13/94
					DWG. SIZE	DWG. NO.	
					A	HO-62-2	